BriMon

Design and Implementation of Railway Bridge Monitoring Application

Hemanth H

Under Guidance of
Dr. Bhaskaran Raman
And
Dr Kameswari Chebrolu



Agenda

- § Introduction to the Problem
- S Application Design
- **S** Transport Protocol
- **S** Routing Protocol
- § Current Status



Agenda

- § Introduction to the Problem
 - § Motivation
 - § Problem Statement
 - § Related Work
 - § Introduction
- § Application Design
- § Transport Protocol
- **S** Routing Protocol
- § Current Status




Motivation

- 20 lakh railway bridges in India of which 43 per cent are 100 years old and 57 per cent 80 years old
- Ø Current State: Monitoring using huge equipment, takes days to setup.
- Analysis done online , data cannot be easily stored.
- Ø Frequent Monitoring next to impossible..

Protocols, Hardware and design may be reusable

Deployments will enable faster Industry adoption



Problem Statement

"The structural <u>response</u> (readings of the accelerometer) of the bridge have to be <u>reliably</u> delivered to a central location for further processing."

Analysis

ØReadings from **piers** of the bridge

ØNo significant **loss** of data

ØSystem should be **fault tolerant**

ØKinds of Vibrations

Ø Forced Vibrations

ØAmbient Vibrations

ØFree Vibrations

Constraints

ØEquipment to run on **battery** power.

ØHostile Environment.

ØUnreliable hardware

ØNo straight forward way to detect passage of train.

Our goal is to build a working prototype



Related Work

Habitat Monitoring

- long term sensor network deployment of 32 Mica2 nodes
- aims to monitor seabird nesting environments
- monitors temperature, pressure, humidity etc,

Industrial Sensor Network:

- predictive equipment maintenance
- aims to replace expensive wireless sytems
- measures acceleration,
- single hop and multi hop.
- long term deployment on micaZ and imotes.

WISDEN:


- multi-hop WSN
- monitoring large structures
- to replace existing wired systems
- 14 micaZ nodes
- measures acceleration
- sampling rate 200-250Hz

ØSingle hop wireless solutions for bridge monitoring availableØUsing WiFi.ØVery expensive

ØRecent efforts by UCLA using sensor nodes and DAQs BriMon Project

Introduction

- MoteIV's Tmote-sky
 - CC2420, 256Kbps
 - 10KB RAM
 - 1MB Flash.
- TinyOS and NesC
 - C like syntax
 - Components
 - Interfaces and Implementation
 - Event based programming.
- Soekris
 - Single board computer
 - Ethernet, WiFi, Serialport
 - Pebble linux










Agenda


- § Introduction to the Problem
- § Application Design
 - § Overview
 - Sequence of Events.
 - S Data Organization and Layering
 - § Alternatives and feasibility
 - § Hardware Design
- **S** Transport Protocol
- **S** Routing Protocol
- § Current Status



Application Design: Overview



Application Design: Overview







802.15.4

Wake-On-WLan



























Data Organization



Layering

Sending Node Receiving Node **Application Layer Application Layer** SendFile.send() SendFile.sendDone() ReceiveFile.receive() Transport Layer Transport Layer Route.getParent() Route.getParent() SendDataMsg. ReceiveDataMsg. Route.parentAssigned() Route.parentAssigned() sendDone() Receive() Routing Layer Routing Layer SendDataMsg.send() **MAC** MAC PHY PHY

Common practice for networking applications

Why do we need layering?

Tiny OS encourages it

An example is use of AM_ messages



BriMon Project

Design Alternatives

- Why not draw power from electric lines on tracks?
 - Not all tracks are electrified.
 - Monitoring needed when bridge getting built.
 - Feasibility not known.
- Use GPRS for data transfer.
 - GPRS not available at most places.
- Use mechanical switch to detect arrival of train
 - Not our area of expertise
 - Still we need another system/device to transfer data.
- Using GPS for synchronization
 - Using GPS at every node is expensive.
 - A GPS device at the base node is feasible



Feasibility

- Earlier deployments on other hardware have run for months.
- Current hardware is better.
- Man power to replace batteries once every 3-6months available.
- WOW tested on long distance link.
- Sensor nodes also tested on 500m link with external antenna.
- Data transfer using WiFi at speeds of 70mph is achieved

Hardware Design

- Accelerometer
 - Is it possible that a MEMS accelerometer replace existing expensive accelerometers?
 - Range 0-50Hz
 - Low power, low noise, high sensitivity.
 - MMA7260Q and ADXL203
 - Fabrication of MMA7260 application circuit (
 PCB Library)
- Attenuator Circuit.
 - To solve the clipping problem



Hardware Design

- Switch Circuit
 - Other devices cannot be shutoff by using a command.
- Is it possible to transfer data from the tmote to the Soekris?
 - USB to Serial?
 - UART to Serial converter
- Power Circuit



Agenda

- § Introduction to the Problem
- § Application Design
- **S** Transport Protocol
 - **S** Choice of Protocol
 - **S** Overview
 - S Protocol description
- **S** Routing Protocol
- § Current Status




Transport Protocol: Overview

- Existing Protocols
 - PSFQ
 - RMST
 - ESRT
- RMST and ESRT no implementation.
- PSFQ implementation for mica, and PSFQ known to perform badly in our setting

- Reliably transfers a file from a node to its parent
- Store, Wait and Forward
- NACK based reliability
- Tight integration with read and write Flash operation
- Only hop-by-hop reliability



Transport Protocol



T_h is the inter file transfer interval


Inserted for handling SPI conflict b/w radio and flash

Td is the inter packet interval


zero packet loss



Transport Protocol




$$T_{hr} = T_{tr}$$






Transport Protocol



$$T_d = T_{retr}$$







Agenda

- § Introduction to the Problem
- S Application Design
- **S** Transport Protocol
- **S** Routing Protocol
 - § Protocol Choice
 - **S** Overview
 - S Protocol Description
- **S** Current Status



Routing Protocol: Overview

ØExisting Protocols

ØSingle Destination DSDV

ØMultiHopLQI

ØMintRoute

ØAll nodes start transmitting beacons simultaneously and continue doing so.

ØMetric used as LQI, but LQI is not a good measure of packet loss


ØBase Node starts the routing process

ØThe protocol does not go on forever.

ØPacket loss is the metric.




Routing Protocol: Brief Description



- NODE_LISTEN
- 2 NODE_TRANSMIT
- 2 NODE_IDLE
- 2 NODE_LEAF




Status



Base Node




Status



Ordinary Nodes




Software Components





- Used existing code in the stack
- Had to be tweaked or changed





Conclusion

- Developed various Hardware and Software components required.
- Successfully able to collect data to a central server (soekris) from the WSN.
- Application is reliable as per our testing so far.
- Protocols developed found almost direct use in WiBeam project.
- Application Design and protocols were used in several CS725 course projects.

Future Work

- Integrating all components.
- Documenting the design and the code.
- Initial outdoor testing.
- Testing on an actual bridge.
- Long term deployment on a bridge.



Thank You

Questions?

