

Graceful Degradation of QoS in Smart Grid

Rohit Gupta
under the guidance of
Prof. Krithi Ramamritham



Department of Computer Science and Engineering
Indian Institute of Technology, Bombay

April 1, 2016

Power Shortage in India

In India electrical power generation is always less than it's demand.

During April 2014 - March 2015

- The gap between requirement and availability of energy was 3.6 %
- The gap between peak demand and supply was 4.7 %

Power Shortage in India

In India electrical power generation is always less than it's demand.

During April 2014 - March 2015

- The gap between requirement and availability of energy was 3.6 %
- The gap between peak demand and supply was 4.7 %

This demand supply gape can be taken care by

Power distribution is different

Utilities impose blackout it is difficult to apply solutions from other systems to Power Grid.

Power distribution is different

Utilities impose blackout it is difficult to apply solutions from other systems to Power Grid.

- Telephony (circuit switching).
Wait is not accepted.

Power distribution is different

Utilities impose blackout it is difficult to apply solutions from other systems to Power Grid.

- Telephony (circuit switching).
Wait is not accepted.
- Internet (packet switching).
Partial bandwidth is not accepted.


Power distribution is different

Utilities impose blackout it is difficult to apply solutions from other systems to Power Grid.

- Telephony (circuit switching).
Wait is not accepted.
- Internet (packet switching).
Partial bandwidth is not accepted.
- Process and memory management (scheduling).
Pause is not accepted.

Brownout

To achieve efficient utilization of power and to avoid blackouts.



Thanks